7.8 Paint

Paint touch-ups can be performed on the unit using a high temperature paint (in aerosol spray can format) by Stove Bright®. Refer to your invoice to determine the precise color of your unit. Contact your local hearth shop for further information on purchasing this paint.

NOTE: Apply the paint in a well ventilated area. If applying paint to the door, properly cover/mask the glass of the door using painters tape and cardboard. Wait for paint to dry before operating the unit. Refer to the instructions on the label of the aerosol spray can for proper paint application. WARNING: Never apply paint to the unit during operation or when it is hot.

7.9 Replacement Parts

Code	Description	Illustration
24SFC_WP	Wood pull handle (specify color)	
PYRO_18.75_13.75	Novo 18 - 18.75" X 13.75" Pyroceram III / Keralite 5mm thick glass	
PYRO_24.875_14.75	Novo 24 - 24.875" X 14.25" Pyroceram III / Keralite 5mm thick glass	
PYRO_24.25_17	Novo 38 - 24.25" X 17" Pyroceram III / Keralite 5mm thick glass	
GSK_0.3125"_8'	Graphite coated square gasket 0.3125" thick X 8' length	
GSK_0.75"_8'	Graphite coated square gasket 0.75" thick X 8' length	
55416.32130	AC tangential blower <u>Electrical rating</u> : 115VAC, 60Hz, 56W <u>Certification</u> : VDE, CSA, UL, CE	
60T22	Thermo-disk <u>Electrical rating</u> : 120VAC, 15A <u>Certification</u> : UL/CSA	

Refer to the codes from the table below for any replacement parts:

B6518	Speed Control <u>Electrical rating</u> : 2.5 Amps, 115VAC – 50/60Hz <u>Certification</u> : UL, ULC	
PA5000	Combustion Air Control (specify color)	
CM0020	Cold Hand Key	C SUIPFRENAIL O
CPSP0301	Removable Ashlip (specify color)	
18SF1175	Soapstone Panel 13" X 10.125" X 1.25"	
18SFC1175	Cast Iron Panel 13" X 10.125" X 1.25"	HHHH HHHH
24SF1175	Soapstone Panel 13" X 11.75" X 1.25"	
24SFC1175	Cast Iron Panel 13" X 11.75" X 1.25"	
38SF1175	Soapstone Panel 16" X 12.625" X 1.25"	
38SFC1175	Cast Iron Panel 16" X 12.625" X 1.25"	